

TA230



Features:

- Support Baytrail Intel Quad Core J1900 2.0 Ghz
- Spilt-proof Full-Flat Touch Screen
- Smart fan cooling system
- Integrated MSR, Customer Display, i-Button Module (Optional)
- Integrated High-Speed Thermal Receipt Printer.
- Space-Saving and Easy Maintenance



Angle adjustable customer display

Integrated high-speed thermal receipt printer

Authorized Reseller

Janz Service Center : 0804 1401 061

JANZ

Machtvoll Pos



Touch Pos

TC230

Features:

- Support Baytrail Intel Quad Core J1900 2.0 Ghz
- Spilt-proof Full-Flat Touch Screen
- Smart fan cooling system
- Integrated MSR, Customer Display, i-Button Module (Optional)
- Integrated High-Speed Thermal Receipt Printer
- Space-Saving and Easy Maintenance



Easy-replacement with modularized HDD and ppherperal

Full flat touch screen LCD display

Operate with less noise and energy saving processor

TC230

Specification (TC230)

System	CPU	bay trail J1900 2.0Ghz, L2 cahce 2MB	
	Memory	DDR3 SO-DIMM (1 slot, up to 8GB)	
	Core Logic	Intel® Bay Trail-D J1900 chipset	
	Network	10/100/1000 Base-T Fast Ethernet	
	Power Supply	90~120 Watt Power Adaptor	
	System Weight	with power adaptor approx. 6.7kg	
	Dimension	391.2(W) x 352.3(H) x 245.0(D)	
	O.S. Support	POSReady2009/windowsXP/POSReady7/ windows7/Linux	
	Storage	Audio	2W Speaker
		SATA	1 x 2.5" HDD or SSD
I/O Ports	USB	1 x USB 3.0, 4 x USB 2.0	
	Serial Ports	4 x DB9,+5V/12V selectable	
	PS/2	1 x PS/2 ports (default at keyboard)	
	LAN	1 x RJ45	
	VGA	1 x DB15	
	Cash Drawer	1 x RJ11 (+12V or +24V selectable)	
	Line out	1 x Phone jack	
	DC-out	1 x 12VDC	
	DC-in	1 x 4pin DC Power Jack	
	Peripheral	Customer Display	VFD, 20 columns and 2 lines
MSR & iButton		ISO I,II,III; JIS I,II and support information key (iButton Optional)	
RFID		ISO14443A, Mifare, Felica-Lite (Optional)	
2nd Display		8" or 10.4" LCD (Optional)	
Fingerprint		8-bit grayscale, reader (Optional)	
LCD		15" TFT LCD	
Display	Max. Resolution	1024 x 768	
	Brightness	300 cd/m ²	
	Touch Screen	Bezel Free Projected Capacitive	
	Tilt Angle	15~80 degrees	

TA230

Specification (TA230)

System	CPU	bay trail J1900 2.0Ghz, L2 cahce 2MB	
	Memory	DDR3 SO-DIMM (1 slot, up to 8GB)	
	Core Logic	Intel® Bay Trail-D J1900 chipset	
	Network	10/100/1000 Base-T Fast Ethernet	
	Power Supply	90~120 Watt Power Adaptor	
	System Weight	with power adaptor approx. 8.5kg	
	Dimension	374(W) x 280(H) x 346(D)	
	O.S. Support	POSReady2009/windowsXP/POSReady7/ windows7/Linux	
	Storage	Audio	2W Speaker
		SATA	1 x 2.5" HDD or SSD
I/O Ports	USB	1 x USB 3.0, 4 x USB 2.0	
	Serial Ports	4 x DB9,+5V/12V selectable	
	PS/2	1 x PS/2 ports (default at keyboard)	
	LAN	ISO I,II,III; JIS I,II and support information key (iButton Optional)	
	VGA	1 x DB15	
	Cash Drawer	1 x RJ11 (+12V or +24V selectable)	
	Line out	1 x Phone jack	
	DC-out	1 x 12VDC	
	DC-in	1 x 4pin DC Power Jack	
	Peripheral	Customer Display	VFD, 20 columns and 2 lines
MSR & iButton		ISO I,II,III; JIS I,II and support information key (iButton Optional)	
RFID		ISO14443A, Mifare, Felica-Lite (Optional)	
2nd Display		8" or 10.4" LCD (Optional)	
Fingerprint		8-bit grayscale, reader (Optional)	
LCD		15" TFT LCD	
Display	Max. Resolution	1024 x 768	
	Brightness	250 cd/m ²	
	Touch Screen	Bezel Free, 5-wire Resistive Touch	
	Tilt Angle	fix 50 degrees	