

# JZ-PT250

SPECIFICATION		PARAMETER
Printing	Printing method	Direct thermal printing
	Resolution	203dpi
	Printing width	72mm
	Printing speed	Max,250mm/s
	Printing density	Adjustable from degree 1 to degree 4
Page mode		YES
Memory	RAM	1Mb
	Flash	4Mb
Character Set	Font	Font A:12*24, Font B 9*17 CHN:24*24
	Alphanumeric	95
	Expanded character	128*30
	International character	15
Graphics		Support bitmap with different density and user defined bitmap (64K for per bitmap, and 256K for total)
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	PDF417, QR code/DataMatrix/Maxicode/Aztec optional
Interface		Default:USB,RS232,Ethernet, drawer Optional:Parallel,WiFi
Detection	Sensor	Paper out detection, paper near end detection,cover open detection
	Input	AC100V~240V 50-60HZ
Power supply	Output	DC 24V±5%,2.0A,±1009-3P interface
Paper	Page type	Standard thermal paper
	Paper width	78.5±0.5mm/57.5±0.5mm
	Paper thickness	0.065~0.1mm
	Paper roll diameter	83mm Max.
	Paper loading	Easy loading
	Paper cutting	Auto cutting or manual cutting
Physical characteristics	Operating condition	5~45 °C (10~95%RH)
	Storage condition	-10~50 °C (10~95%RH)
	Dimension	195(L)*147(W)*147(H)mm
	N. W.	1.5kg (without paper roll)
Reliability	TPH life	150mm
	Cutter life	2,000,000 times
	Motor life	50,000,000 lines
Firmware	Emulation	ESC/POS
	Software	Driver
		Windows 2000/ XP /Vista /7 /8 /POSReady Linux, OPOS

Authorized Reseller



Janz Service Center : 0804 1401 061

**JANZ**  
Machtvoll Printer



Label Printer

# JZ-PT350

SPECIFICATION		PARAMETER
Printing	Printing method	Direct thermal printing
	Resolution	203dpi
	Printing width	72mm
	Printing speed	Max,300mm/s
	Printing density	Adjustable from degree 1 to degree 4
Page mode		YES
Memory	RAM	1Mb
	Flash	4Mb
Character Set	Font	Font A:12*24, Font B 9*17 CHN:24*24
	Alphanumeric	95
	Expanded character	128*30
	International character	15
Graphics		Support bitmap with different density and user defined bitmap (64K for per bitmap, and 256K for total)
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	PDF417, QR code/DataMatrix/Maxicode/Aztec optional
Interface		Default:USB,drawer,Optional:Parallel,RS232, Ethernet,Bluetooth
Detection	Sensor	Paper out, paper near end, and paper jam detection, cover open detection
	Input	AC100V~240V 50-60HZ
Power supply	Output	DC 24V±5%,2.0A,±1009-3P interface
Paper	Page type	Standard thermal paper
	Paper width	78.5±0.5mm/57.5±0.5mm
	Paper thickness	0.065~0.1mm
	Paper roll diameter	83mm Max.
	Paper Loading	Easy Loading
	Paper cutting	Auto cutting or manual cutting
Physical characteristics	Operating condition	5~40 °C (10~95%RH)
	Storage condition	-10~50 °C (10~95%RH)
	Dimension	191(L)*130(W)*131(H)mm
	N. W.	1.53kg (without paper roll)
Reliability	TPH life	150mm
	Cutter life	2,000,000 times
	Motor life	50,000,000 lines
Firmware	Emulation	ESC/POS
	Software	Driver
		Windows 2000/ XP /Vista /7 /8 /POSReady Linux, OPOS

# JZ-PT350



Colorful LED indicators

Status LED	Specification
White	Printer Power On
Green	Printer is ready in its condition
Red	Wrong Status (Out of paper,cover open, and so on)
Red+Pink	Paper near end and printer is in normal
Blue	Printer is busy

Splash proof



Cutter jam auto-eliminating design



Plug-in connected port  
plug-in connected port design,  
Multi interfaces can  
be interchanged quickly



# JZ-PT250

Cover out sensor, paper out sensor

Double horizontal auto-cutter  
1 cutter to 2 cutters (just like long scissor and short scissor) shorter arm of force improves the cutting effect and cutter life greatly

Default Combo Interfaces  
Optional Wifi, Bluetooth and Parallel interface

Metallic printer enclosure (metal frame mechanism), similar concept with Epson, better heat dissipation than plastic structure, ensure good printing quality and improve TPH lift time